




## 350-ALTBRKT-C REV A INSTALL INSTRUCTIONS

PART	QTY	APPLICATION
5/16-18 x 1.0" BHCS	1	Alternator Tensioning Bolt
3/8-16 X .75" SHCS	2	Bracket to Water Pump
3/8-16 X 6.0" SHCS	1	Bracket and Alternator to head
6257722-325 (3.25" Spacer)	1	Spacer between alternator and head
350522-C	1	Main Bracket
<b>Total</b>	<b>6</b>	



QUESTIONS ABOUT YOUR INSTALL? CONTACT US AT [SUPPORT@CVFRACING.COM](mailto:SUPPORT@CVFRACING.COM) or 651.356.8593

CVF RACING® | 618 6TH STREET NW | NEW PRAGUE MN 56071 | [CVFRACING.COM](http://CVFRACING.COM)



## 350-ALTBRKT-C REV A INSTALL INSTRUCTIONS

**Step 1:** Remove old alternator brackets

**Step 2:** Attach alternator bracket to water pump using the (2) 3/8 X .75" SHCS. Do not fully tighten.

**Step 3:** Attach the alternator through the top hole. The alternator will sit flush against the bracket and have the 3.25" spacer between it and the cylinder head. Secure with the 3/8 X 6" SHCS. All bolts can now be tightened to spec.

**Step 4:** The 5/16 X 1" BHCS is used to hold the alternator to the bracket. Do not tighten completely until your system is fully installed as this will slide to left to increase tensioner and right to decrease.

**Step 5:** Install belt. This bracket is used for both V-Belt (15/32" wide at the top) and serpentine (8 Rib) applications. The best place to find proper belt routing for your specific kit is [cvfracing.com](http://cvfracing.com).

### Torques Specs:

All torque specs can be found on the last page of this instruction packet provided by Fastenal. We have highlighted all CVF bolts inside the table. Feel free to keep the page and use it for reference in your garage.

**Note:** Metric Socket Head Bolts are not listed. Use the recommended torque specs for 5/16 when tightening M8 bolts and 3/8 torque specs when tightening M10.

Thank you for your purchase from CVF Racing! If you have any questions about your install, check out our support center for install guides, videos, and other helpful tips. If you need further help, our tech staff can be reached M-F from 8-5 PM CST via phone, email, or chat.

**Looking to upgrade further?** Contact us to upgrade your system! Most can be added with little to no modification of your installed kit.

- Add AC and Power Steering (Serpentine)
- Add new high flow cast water pump
- Add new GM Alternator
- Add new Saginaw Style Power Steering Pump
- Add Power Steering (V-Belt)
- Hood Hinges



# 350-ALTBRKT-C REV A INSTALL INSTRUCTIONS

## METRIC FASTENERS

Nominal Dia. (mm)	Pitch	4.6 Class 4.6						8.8 Class 8.8						10.9 Class 10.9						12.9 Class 12.9						
		Clamp Load (lbs)			Tightening Torque			Clamp Load (lbs)			Tightening Torque			Clamp Load (lbs)			Tightening Torque			Clamp Load (lbs)			Tightening Torque			
		K = 0.15	K = 0.17	K = 0.20	K = 0.15	K = 0.17	K = 0.20	K = 0.15	K = 0.17	K = 0.20	K = 0.15	K = 0.17	K = 0.20	K = 0.15	K = 0.17	K = 0.20	K = 0.15	K = 0.17	K = 0.20	K = 0.15	K = 0.17	K = 0.20	K = 0.15	K = 0.17	K = 0.20	
4	0.7	333	7.9 in-lbs	8.9 in-lbs	10.5 in-lbs	858	20.3 in-lbs	23 in-lbs	27 in-lbs	1228	29 in-lbs	32.9 in-lbs	38.7 in-lbs	1436	33.9 in-lbs	38.4 in-lbs	45.2 in-lbs									
5	0.8	538	15.9	18.0	21.2	1387	40.9	46.4	54.6	1985	58.6	66.4	78.1	2319	68.5	77.6	91.3									
6	1	763	27.0	30.7	36.1	1968	69.7	79.0	92.9	2816	99.8	113.1	133.0	3291	116.6	132.1	155.4									
7	1	1095	45.3	51.3	60.3	2822	116.6	132.2	155.5	4039	167	189	223	4720	195	221	260									
8	1.25	1389	65.6	74.4	87.5	3580	169.1	191.6	225.4	5123	242	274	323	5987	283	320	377									
10	1.5	2200	10.8 ft-lbs	12.3 ft-lbs	14.4 ft-lbs	5671	27.9 ft-lbs	31.6 ft-lbs	37.2 ft-lbs	8115	39.9 ft-lbs	45.2 ft-lbs	53.2 ft-lbs	9484	46.7 ft-lbs	52.9 ft-lbs	62.2 ft-lbs									
12	1.75	3197	18.9	21.4	25.2	8240	48.7	55.1	64.9	11792	69.6	78.9	92.8	13781	81.4	92.2	108.5									
14	2	4379	30.2	34.2	40.2	11289	77.8	88.1	103.7	16154	111.3	126.1	148.4	18879	130.0	147.4	173.4									
16	2	5943	47	53	62	15320	121	137	161	21924	173	196	230	25622	202	229	269									
18	2.5	7301	65	73	86	18822	167	189	222	26934	239	270	318	31477	279	316	372									
20	2.5	9286	91	104	122	23938	236	267	314	34256	337	382	449	40034	394	446	525									
22	2.5	11509	125	141	166	29669	321	364	428	42457	460	521	613	49619	537	609	716									
24	3	13372	158	179	211	34471	407	461	543	49329	582	660	777	57649	681	771	908									
27	3	17428	232	262	309	44924	597	676	796	64288	854	968	1139	75132	998	1131	1331									
30	3.5	21266	314	356	419	54819	809	917	1079	78448	1158	1312	1544	91680	1353	1534	1804									
33	3.5	26310	427	484	570	67821	1101	1248	1468	97055	1576	1786	2101	113425	1842	2087	2455									
36	4	30982	549	622	732	79866	1415	1603	1886	114291	2024	2294	2699	133569	2366	2681	3154									

\* Tightening Torque (in-lbs through M8; M10 & over ft-lbs)

## TORQUE-TENSION RELATIONSHIP FOR A307A, GRADE 5, 8 & 9 BOLTS

Nominal Dia. (in.)	Threads per inch	307A ASTM A307 Grade A						SAE J429 Grade 5						SAE J429 Grade 8						FNL Grade 9					
		Clamp Load (lbs)			Tightening Torque			Clamp Load (lbs)			Tightening Torque			Clamp Load (lbs)			Tightening Torque			Clamp Load (lbs)			Tightening Torque		
		K = 0.15	K = 0.17	K = 0.20	EcoGuard™	K = 0.15	K = 0.17	K = 0.20	EcoGuard™	K = 0.15	K = 0.17	K = 0.20	EcoGuard™	K = 0.15	K = 0.17	K = 0.20	EcoGuard™	K = 0.15	K = 0.17	K = 0.20	EcoGuard™	K = 0.15	K = 0.17	K = 0.20	
Coarse Thread Series																									
1/4	20	859	32 in-lbs	37 in-lbs	43 in-lbs	2029	61 in-lbs	76 in-lbs	86 in-lbs	10 in-lbs	2864	86 in-lbs	107 in-lbs	122 in-lbs	143 in-lbs	3357	101 in-lbs	126 in-lbs	143 in-lbs	168 in-lbs					
5/16	18	1416	66	75	88	3342	125	157	178	209	4719	177	221	251	295	5531	207	259	294	346					
3/8	16	2092	10 ft-lbs	11 ft-lbs	13 ft-lbs	4940	19 ft-lbs	23 ft-lbs	26 ft-lbs	31 ft-lbs	6974	26 ft-lbs	33 ft-lbs	37 ft-lbs	44 ft-lbs	8174	31 ft-lbs	38 ft-lbs	43 ft-lbs	51 ft-lbs					
7/16	14	2870	16	18	21	6777	30	37	42	49	9568	42	52	59	70	11214	49	61	70	82					
1/2	13	3831	24	27	32	9046	45	57	64	75	12771	64	80	90	106	14969	75	94	106	125					
9/16	12	4912	35	39	46	11599	65	82	92	109	16375	92	115	130	154	19193	108	135	153	180					
5/8	11	6102	48	54	64	14408	90	113	128	150	20340	127	159	180	212	23840	149	186	211	248					
3/4	10	9030	85	96	113	21322	160	200	227	267	30101	226	282	320	376	35281	265	331	375	441					
7/8	9	12467	136	155	182	29436	258	322	365	429	41556	364	455	515	606	48707	426	533	604	710					
1	8	16355	204	232	273	38616	386	483	547	644	54517	545	681	772	909	63899	639	799	905	1065					
1-1/4	7	26166	409	463	545	53786	672	840	952	1121	87220	1090	1363	1545	1817	102229	1278	1597	1810	2130					
1-3/8	6	31182	536	607	715	64096	881	1102	1249	1469	103939	1429	1768	2025	2382	121826	1675	2094	2373	2792					
1-1/2	6	37942	711	806	949	77991	1170	1462	1657	1950	126473	1897	2371	2688	3162	148237	2224	2779	3150	3706					
Fine Thread Series																									
1/4	28					2319	70 in-lbs	87 in-lbs	99 in-lbs	116 in-lbs	3274	98 in-lbs	123 in-lbs	139 in-lbs	164 in-lbs	3837	115 in-lbs	144 in-lbs	163 in-lbs	192 in-lbs					
5/16	24					3702	139	174	197	231	5226	196	245	278	327	6125	230	287	325	383					
3/8	24					5599	21 ft-lbs	26 ft-lbs	30 ft-lbs	35 ft-lbs	7905	30 ft-lbs	37 ft-lbs	42 ft-lbs	49 ft-lbs	9265	35 ft-lbs	43 ft-lbs	49 ft-lbs	58 ft-lbs					
7/16	20					7568	33	41	47	55	10684	47	58	66	78	12523	55	68	78	91					
1/2	20					10197	51	64	72	85	14396	72	90	102	120	16873	84	105	120	141					
9/16	18					12940	73	91	103	121	18268	103	128	146	171	21412	120	151	171	201					
5/8	18					16317	102	127	144	170	23036	144	180	204	240	27000	169	211	239	281					
3/4	16					23776	178	223	253	297	33566	252	315	357	420	39343	295	369	418	492					
7/8	14					32479																			